

S-200

Cuts steel materials as well as cables up to 20 mm



S-200



S-200 (Latch opened)

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and latch type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 235 N
 Single stage pumping
 Relief valve is not equipped
 Reservoir capacity : 60 cc
 Maximum opening : 22 mm
 Pumping cycles when no load : 39 times

Output force : 66 kN

SIZE

400 (L) mm

WEIGHT

3.0 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 16 mm
Wire rope 6 x 12	: 20 mm
Wire rope 6 x 19	: 20 mm
Soft steel bar	: 16 mm
Reinforcing rod	: 13 mm
Cu strands	: 20 mm
Al strands	: 20 mm
ACSR	: 21 mm
Guy wire 1 x 7	: 16 mm
Guy wire 1 x 19	: 16 mm
CCP cable	: N/A

MODEL No.

S-240

Cuts steel materials as well as cables up to 24 mm



S-240



S-240 (Latch opened)

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and latch type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 226 N
 Two stage pumping
 Relief valve is not equipped
 Reservoir capacity : 120 cc
 Maximum opening : 24 mm
 Pumping cycles when no load : 13 times

Output force : 84 kN

SIZE

475 (L) mm

WEIGHT

4.9 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 18 mm
Wire rope 6 x12	: 24 mm
Wire rope 6 x 19	: 24 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 24 mm
Al strands	: 24 mm
ACSR	: 24 mm
Guy wire 1 x7	: 20 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A


MODEL No.

S-320

Cuts heavy steel materials up to 32 mm



S-320



S-320 shown with Reinforcing rod

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Safety relief valve for overload protection
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and latch type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 276 N
 Two stage pumping
 Relief valve is equipped
 Reservoir capacity : 202 cc
 Maximum opening : 35 mm
 Pumping cycles when no load : 20 times

Output force : 191 kN

SIZE

580 (L) mm

WEIGHT

12.0 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 32 mm
Wire rope 6 x12	: 32 mm
Wire rope 6 x 19	: 32 mm
Soft steel bar	: 25 mm
Reinforcing rod	: 25 mm
Cu strands	: 32 mm
Al strands	: 32 mm
ACSR	: 32 mm
Guy wire 1 x7	: 32 mm
Guy wire 1 x 19	: 32 mm
CCP cable	: N/A

MODEL No.

S-400

Cuts steel materials as well as cables up to 41 mm



S-400



S-400 (Head opened)

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 196 N
 Two stage pumping
 Relief valve is not equipped
 Reservoir capacity : 120 cc
 Maximum opening : 42 mm
 Pumping cycles when no load : 17 times

Output force : 68 kN

SIZE

575 (L) mm

WEIGHT

5.8 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 22 mm
Wire rope 6 x12	: 25 mm
Wire rope 6 x 19	: 25 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 41 mm
Al strands	: 41 mm
ACSR	: 38 mm
Guy wire 1 x7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A

MODEL No.

S-550

Cuts steel materials as well as cables up to 54 mm



S-550



S-550 (Head opened)

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Safety relief valve for overload protection
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 276 N
 Two stage pumping
 Relief valve is equipped
 Reservoir capacity : 202 cc
 Maximum opening : 54 mm
 Pumping cycles when no load : 25 times

Output force : 120 kN

SIZE

625 (L) mm

WEIGHT

10.0 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 25 mm
Wire rope 6 x12	: 30 mm
Wire rope 6 x 19	: 30 mm
Soft steel bar	: 22 mm
Reinforcing rod	: 20 mm
Cu strands	: 54 mm
Al strands	: 54 mm
ACSR	: 54 mm
Guy wire 1 x7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A

MODEL No.

850

Cuts cables up to 85 mm



850



850 (Head opened)

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 196 N
 Two stage pumping
 Relief valve is not equipped
 Reservoir capacity : 120 cc
 Maximum opening : 88 mm
 Pumping cycles when no load : 20 times

Output force : 40 kN

SIZE

710 (L) mm

WEIGHT

8.2 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Cu strands	: 28 mm
Al strands	: 38 mm
CCP cable	: 85 mm

Wire rope 6 x 7	: N/A
Wire rope 6 x 12	: N/A
Wire rope 6 x 19	: N/A
Soft steel bar	: N/A
Reinforcing rod	: N/A
ACSR	: N/A
Guy wire 1 x 7	: N/A
Guy wire 1 x 19	: N/A

MODEL No.

S-32CC1

Soft steel bar : 19 mm Re-bar : 19 mm

Al or Cu rod : 25 mm



S-32CC1



S-32CC1 (Latch opened)

FEATURES

The S-32CC1 hydraulic cutter was specially designed to cut the toughest EHS guy wire, ground and anchor rods.

The anvil style, center cut blades eliminate jamming problems common to shear type cutters, and the blades are easily replaced in the field.

The tool is made of high grade steel and has rubber handle grips.

A flip-top latch opens the tool jaw to accept material to cut easily.

SPECIFICATIONS

Maximum handle force : 284 N

Reservoir capacity : 165 cc

No relief valve equipped

Output force : 191 kN

SIZE

685 (L) mm

WEIGHT

10.2 kg

ACCESSORIES

Carrying bag

REMARKS

* Heavy duty head design

* Easily replaceable blades

* Butting type cut for solid materials (Chain, Steel bar, Guy wire, Re-bar)

* Flip-top latch for easy insertion of cutting material